

Date:	_____
Project:	_____
Price:	_____

LED CENTER BASKET TROFFER

Description:

Our LED Center Basket Troffer is your classic recessed troffer which gives off a consistent and balanced light scheme, brightening up any room. Coming in a variety of size and CCT options, this fixture is perfect for any application, ranging from offices to retail stores.



Features:

- Input Voltage: AC120-277V, 50/60Hz
- Power Consumption: See Ordering Key.
- Lumens Output: 130 Lm/W
- CRI >90
- Available CCT Options: 3000K, 3500K, 4000K, or 5000K
- Available Sizes: 2' x 2' or 2' x 4'
- Compatible with standard and narrow T-grids.
- Slanted troffer reduces glare and provides even light distribution.
- 0-10V dimmable option available.
- Lighting controls option available.
- L70 Lifetime: >50,000 hours
- 7 Year Warranty

Applications:

- Retail Stores
- Offices
- Schools
- Libraries
- Hospitals
- Gyms



Dimensions:



	L	W	H
2*2FT	23.7"	23.7"	4.0"
2*4FT	47.25"	23.75"	2.63"



Date:	_____
Project:	_____
Price:	_____

Ordering Key New Construction:

SERIES NUMBER	WATTS / SIZE / LUMENS	CCT	FINISH	ADDITIONAL OPTIONS
ILCLLT	30w22 - 2x2 / 3,766	3 - 3000K		DM - 0-10V DIMMABLE
	32w22 - 2x2 / 4,371	35 - 3500K		EM - EMERGENCY BACKUP
	42w22 - 2x2 / 4,365	4 - 4000K		SM - SURFACE MOUNT
	39w24 - 2x4 / 4,945	5 - 5000K		FM - FLANGE MOUNT
	44w24 - 2x4 / 5,794			CM - CABLE MOUNT
	52w24 - 2x4 / 5,918			

SAMPLE ITEM NUMBER: ILCLLT 30W22 4 DM

Ordering Key Retrofits:

SERIES NUMBER	WATTS / SIZE / LUMENS	CCT	FINISH	ADDITIONAL OPTIONS
ILCLLT	23w22 - 2x2 / 3,000	35 - 3500K		DM - 0-10V DIMMABLE
	33w22 - 2x2 / 4,158	4 - 4000K		EM - EMERGENCY BACKUP
	23w24 - 2x4 / 3,036	5 - 5000K		SM - SURFACE MOUNT
	42w24 - 2x4 / 5,376			FM - FLANGE MOUNT
				CM - CABLE MOUNT

SAMPLE ITEM NUMBER: ILCLLT 33W24 5 DM



Date:	_____
Project:	_____
Price:	_____

Electrical Data:

- **Input power:** Stays consistent over life
- **Input Voltage:** AC120-277V
- **CRI:** >90
- **Life Expectancy:** ~50,000 hours

Controls:

- This LED fixture can be equipped with a 0-10V dimming driver that works universally with any standard 0-10V control or dimmer.

Optical System:

- A unique combination of reflective & refractive optical components achieves a uniform, comfortable look while eliminating pixelation & color fringing.
- Parts work in unison to optimize light distribution, balancing the high delivery of high illuminance levels on horizontal surfaces with an ideal amount of light on walls and vertical surfaces, increasing perception of spaciousness.

Photometrics:

