



**i-LUMINOSITY**  
LED LIGHTING FIXTURES

Date:	_____
Project:	_____
Price:	_____

## LED Full Cutoff Wall Pack

### Description:

i-Luminosity's LED Full Cutoff Wall Pack comes in a dark bronze or a black finish suitable for outdoor locations. Wattage options range from 30W-135W with color options 4000K or 5000K. This wall pack is suitable for emergency backup, photocell, and motion sensor.

### Features:

- Input Power: 120-277VAC
- Power Consumption: 30W - 135W
- Lumen Output: 3,300 Lm - 14,500 Lm
- Lighting controls option available.
- CRI >90
- L70 Lifetime: >50,000 hours.
- Available Mounting Options: Wall mounted.
- Available Color Options: 4000K or 5000K.
- Available Finish Options: Black or Dark Bronze
- Type III polycarbonate optical lens
- IP Rating: IP65
- 0-10V Dimmable, Photocell, & Motion Sensor available.
- 7 Year Warranty.
- Dimensions: 14.25" x 7.6" x 9.25"

### Medium size: 30W/45W/70W




### Large size: 90W or 135W



### Applications:

- Wet Location/ Outdoor
- Warehouses
- Parking Lots
- Storage








**i-LUMINOSITY**  
LED LIGHTING FIXTURES

Date: \_\_\_\_\_  
Project: \_\_\_\_\_  
Price: \_\_\_\_\_

## Dimensions:




Unit: IN/MM

Medium Size



Weight  
45W: 9.85lb  
70W: 9.81lb


Large Size



Weight  
90W: 12.98lb  
135W: 13.51lb


## Photometrics:

Medium size  
Luminous Intensity Distribution Curve



Average Diffuse Angle(50%): 102.7°

Large size  
Luminous Intensity Distribution Curve



Average Diffuse Angle(50%): 109.7°



Date:	_____
Project:	_____
Price:	_____

## Ordering Key:

SERIES NUMBER	WATTS / SIZE / LUMENS	CCT	FINISH	ADDITIONAL OPTIONS
ILMSFCWP	30w - 14.2IN / 3,300	4 - 4000K	B - BLACK	EM - EMERGENCY BACKUP
	45w - 14.2IN / 4,900	5 - 5000K	DB - DARK BRONZE	MS - MOTION SENSOR
	70w - 14.2IN / 7,400			DM - 0-10V DIMMING
	90w - 18.1IN / 9,900			PH - PHOTOCCELL
	135w - 18.1IN / 14,500			

SAMPLE ITEM NUMBER: ILMSFCWP 45 4 B EM

## Electrical Data:

- **Input Power:** Stays consistent over life.
- **Input Voltage:** 120-277 VAC
- **CRI:** >90
- **L70 Lifetime:** >50,000 hours.

## Controls:

- This LED fixture can be equipped with 0-10V dimming that works universally with any standard 0-10V control or dimmer.

## Optical System:

- A unique combination of reflective & refractive optical components achieves a uniform, comfortable look while eliminating pixelation & color fringing.
- Parts work in unison to optimize light distribution, balancing the high delivery of high illuminance levels on horizontal surfaces with an ideal amount of light on walls and vertical surfaces, increasing perception of spaciousness.

