

Date: .	
Project:	:
Price:	
_	

## **LED Instafit Tubes:**

## **Description:**

i-Luminosity's Instafit Tubes provide ample lighting or can be directed to a specific location. Available in 3000K, 4000K, or 5000K. Perfect for damp locations, IP20 rating for retrofits or standard fixtures.

#### **Features:**

AC 100-277V

• Rated life: 50,000 hours

• CRI>90

Available in 3000K, 4000K, 5000K.

• Beam Angle: 120

• Operating temperature: -5F - 104F

• 7 Year Warranty.

• Dimensions: 3FT or 4FT



# \*\* Ballast Compatible LED Tube \*\* \*\*In order to the contract of the top in private human\*\* \*\*In order to the contract of the top in private human\*\* \*\*In order to the contract of the top in private human\*\* \*\*In order to the contract of the top in private human\*\* \*\*In order to the contract of the top in private human\*\* \*\*In order to the contract of the top in private human\*\* \*\*In order to the contract of the top in private human\*\* \*\*In order to the contract of the top in private human\*\* \*\*In order to the contract of the top in private human\*\* \*\*In order to the contract of the top in private human\*\* \*\*In order to the contract of the top in private human\*\* \*\*In order to the contract of the top in private human\*\* \*\*In order to the contract of the top in private human\*\* \*\*In order to the contract of the top in the contract of the top in the contract of the top in the contract of the contra



#### **Installation:**

- Type AB tube works with ballast or without.
  - For new construction installations, simply connect the 120-277V line voltage directly to the sockets.
  - For retrofit installations, you may bypass the existing ballast or not by cutting the wires and connecting the 120-277V line voltage directly to the sockets. No ballast or driver is required.





















Date:	
Project:	
Price:	
-	

# **Ordering Key:**

ILTBITWS				
SERIES NUMBER	WATTS/ SIZE/ LUMENS	ССТ	FINISH	ADDITONAL OPTIONS
ILTBITWS	<b>12W4 -</b> 4FT / 1,680	<b>3K</b> - 3000K		
	15W3 - 3FT / 2,100	<b>4K</b> - 4000K		
	<b>15W4</b> - 4FT / 2,100	<b>5K</b> - 5000K		

SAMPLE ITEM NUMBER: ILTBITWS 12W3 4K

### **Electrical Data:**

• Input power: Stays consistent over life

• Input Voltage: 100-277V

• Operating Temperature: -5F ~ 104F

• **CRI:** >90

• **Life Expectancy:** ~50,000 hours

# **Optical System:**

- A unique combination of reflective & refractive optical components achieves a uniform, comfortable look while eliminating pixelation & color fringing.
- Parts work in unison to optimize light distribution, balancing the delivery of lighting levels on horizontal surfaces with an ideal amount of light on walls and vertical surfaces, increasing perception of spaciousness.

















