

Date:	_____
Project:	_____
Price:	_____

LED WRAP FIXTURE



FEATURES:

- Available in 4FT or 8FT
- 100% prismatic acrylic lense, 2 LED lamps
- Wattage options: 30W, 32W, 60W, 64W.
- Additonal options: Dimming, Emergency Backup
- A low profile design providing energy efficient lighting
- Mounting options: Suspended or Surface mounted
- Pre-paint: metal parts treated with a multi-stage phosphate bonding process to ensure adhesion & inhibit rusting.
- Reflectance factor exceeding 87% for premium quality and durability.
- 7 Year warranty

SERIES NUMBER	WATTS/ SIZE/ LUMENS	CCT	DRIVER	ADDITIONAL OPTIONS
ILWRWRSL	30W - 4 FT / 4,200	3 - 3000K	I - INTERNAL	DIM - 1-10V DIMMING
	32W - 4 FT / 4,480	4 - 4000K	E* - EXTERNAL	EM - EMERGENCY BACKUP
	60W - 8 FT / 8,400	5 - 5000K		
	64W - 8 FT / 8,960			

SAMPLE ITEM NUMBER: ILWRWRSL 32W 4 E EM

E* - T24 compliant available for 32W or 64W





Date:	_____
Project:	_____
Price:	_____

Electrical Data:

- **Input power:** Stays consistent over life
- **Input Voltage:** 100-277VAC
- **Operating Temperature:** -40°F ~ 104°F
- **CRI:** >90
- **L70 Lifetime:** >50,000 hours

Controls:

- This LED fixture is equipped with a 0-10V dimming driver that works universally with any standard 0-10V control or dimmer.
- This product can be equipped with a motion sensor option.

Optical System:

- A unique combination of reflective & refractive optical components achieves a uniform, comfortable look while eliminating pixelation & color fringing.
- Parts work in unison to optimize light distribution, balancing the high delivery of high illuminance levels on horizontal surfaces with an ideal amount of light on walls and vertical surfaces, increasing perception of spaciousness.

