

Date:	_____
Project:	_____
Price:	_____

# VAPOR TIGHT FIXTURE

## Description:

This Vapor Tight fixture is engineered for performance down to the smallest detail. With a gasket enclosure designed for damp or wet locations, indoors and outdoors, IP65. The clear impact-resistance polycarbonate lens can withstand most harsh environments. The low profile makes it ideal for tight areas and low ceilings.

## Features:

- Material: High impact polycarbonate diffuser and ABS base, lens and 8 snap latches, 2 stainless steel mounting brackets.
- Type: Moisture resistance fixture.
- Voltage: 120VAC
- Available Mounting: Surface, or suspended.
- Reinforced fiberglass body is rugged and corrosion resistant.
- One-piece upper body, no seams to crack, break or leak 5VA Flammability rating.
- Latches designed to accept screws to make enclosure tamper-resistant.
- White polyethylene molded end plugs for use as knockouts.
- High gloss, baked enamel reflective front.
- Optional: Emergency backup; clear lens.
- NSF approved
- IP65
- 7 year warranty.



Sizes: 4ft: 50"L x 7.75"W x 4.75" D  
8ft: 98"L x 7.75" W x 4.75" D

## Applications:

- Food handling & processing facilities
- Refrigerated storage
- Drug and chemical plants
- Shower areas
- Parking garages
- Roadway/ pedestrian tunnels
- Outdoor public areas



Date:	_____
Project:	_____
Price:	_____

## Ordering Key:

SERIES NUMBER	WATTS/ SIZE/ LUMENS	CCT	DRIVER	ADDITIONAL OPTIONS
ILSLVTVT	30W - 4 FT / 4,200	3 - 3000K	I - INTERNAL	EM - EMERGENCY BACKUP
	32W - 4 FT / 4,480	4 - 4000K	E* - EXTERNAL	MS - MOTION SENSOR
	45W - 4FT/ 6,075	5 - 5000K		DM - 0-10V DIMMING
	60W - 8 FT / 8,400			
	64W - 8 FT / 8,960			

SAMPLE ITEM NUMBER: ILSLTVT 32 4 I EM

E\* - T24 compliant available for 32W or 64W

## Electrical Data:

- **Input Power:** Stays consistent over life.
- **Input Voltage:** 120-277 VAC
- **CRI:** >90
- **L70 Lifetime:** >50,000 hours.

## Controls:

- This LED fixture can be equipped with 0-10V dimming that works universally with any standard 0-10V control or dimmer.

## Optical System:

- A unique combination of reflective & refractive optical components achieves a uniform, comfortable look while eliminating pixelation & color fringing.
- Parts work in unison to optimize light distribution, balancing the high delivery of high illuminance levels on horizontal surfaces with an ideal amount of light on walls and vertical surfaces, increasing perception of spaciousness.

