

VAPOR TIGHT FIXTURE FOR COOLERS, WAREHOUSE & OUTDOOR USE

- EMERGENCY BACKUP AVAILABLE
- CLEAR LENS AVAILABLE



FEATURES:

This vapor tight fixture is engineered for performance down to the smallest detail. The gasketed enclosure is designed for damp or wet locations, indoors and outdoors. The clear impact-resistance polycarbonate lens can withstand most harsh environments. The low profile makes it ideal for tight areas and low ceilings. This rugged fixture operates two or three (per 4FT) LED 18 Watt lamps.

CONSTRUCTION:

- Material: High impact polycarbonate diffuser and ABS base, lens and 10 snap latches, 2 stainless steel mounting brackets
- Type: Moisture resistance fixture
- One-piece upper body, no seams to crack, break or leak
- Reinforced fiberglass body is rugged and corrosion resistant
- 5VA Flammability rating
- Latches designed to accept screws to make enclosure tamper-resistant
- White polyethylene molded end plugs for use as knockouts
- High gloss, baked enamel reflective front



INSTALLATION:

- Shipped fully wired
- Easy access to wiring compartment via removable gear tray
- Gear tray tethered to housing by two lanyards for extra safety
- Knockout on each end
- Spring-mount, stainless steel bracket allows for surface or chain mount
- Brackets install first then snap securely onto fixture
- NEC compliant luminaire power disconnect standard

LISTINGS:

UL listed. CE, ROHS compliant

LED VAPOR TIGHT FIXTURE							
ITEM #	SIZE	DRIVER	VOLTAGE	WATT	LUMEN OUTPUT	DIMMING	COLOR
SWWOR4FTVP2L	4 FT	INTERNAL	AC 110 / 277V	36W	4,140	AVAIL	3000K/4000K 5000K/6000K
SWWOR4FTVP3L	4 FT	INTERNAL	AC 110 / 277V	54W	6,210	AVAIL	3000K/4000K 5000K/6000K
SWWOR8FTVP4L	8 FT	INTERNAL	AC 110 / 277V	72W	8,280	AVAIL	3000K/4000K 5000K/6000K
SWWOR8FTVP6L	8 FT	INTERNAL	AC 110 / 277V	108W	12,420	AVAIL	3000K/4000K 5000K/6000K

