

LAY-IN LED TROFFER

EMERGENCY BACK-UP AVAILABLE



2x2: 24" W x 24" D x 4 13/16"H



2x4: 48" W x 24" D x 4 13/16"H

FEATURES:

- **WIRING & ELECTRICAL:** Fixture conforms to UL 1570 and is suitable for damp locations. AWM, TFN, THHN wire used throughout, rated for required temperatures.
- **MATERIALS:** Housing formed from cold-rolled steel. Louvers formed from premium-grade aluminum lighting sheet. No asbestos is used in this product.
- **FINISH:** Five-stage iron-phosphate pretreatment ensures superior paint adhesion and rust resistance. Painted parts finished with high-gloss, baked white enamel.
- **LISTING:** UL listed and labeled. Listed and labeled to comply with Canadian and Mexican Standards
- Specification grade, parabolic unit with superior detailing and finish, offers desirable alternatives to standard and recess lighting while reducing glare and increasing operating efficiency.
- An ideal luminaire for offices, conference rooms and other commercial applications.
- Versatile low-profile design reduces potential height restriction issues.
- Available with multiple air functions.
- Available in multiple sizes with various louver options.



AVAILABLE



| LAY IN TROFFER | | | | | | | |
|-----------------|------|----------|---------------|------|--------------|---------|-------|
| ITEM # | SIZE | DRIVER | VOLTAGE | WATT | LUMEN OUTPUT | DIMMING | COLOR |
| SWWOR2X2TRF3L30 | 2x2 | INTERNAL | AC 110 / 277V | 30W | 3,200 | AVAIL | 3000K |
| SWWOR2X2TRF3L40 | 2x2 | INTERNAL | AC 110 / 277V | 30W | 3,200 | AVAIL | 4000K |
| SWWOR2X2TRF3L50 | 2x2 | INTERNAL | AC 110 / 277V | 30W | 3,200 | AVAIL | 5000K |
| SWWOR2X2TRF4L30 | 2x2 | INTERNAL | AC 110 / 277V | 40W | 4,250 | AVAIL | 3000K |
| SWWOR2X2TRF4L40 | 2x2 | INTERNAL | AC 110 / 277V | 40W | 4,250 | AVAIL | 4000K |
| SWWOR2X2TRF4L50 | 2x2 | INTERNAL | AC 110 / 277V | 40W | 4,250 | AVAIL | 5000K |
| SWWOR2X4TRF3L30 | 2x4 | INTERNAL | AC 110 / 277V | 54W | 5,500 | AVAIL | 3000K |
| SWWOR2X4TRF3L40 | 2x4 | INTERNAL | AC 110 / 277V | 54W | 5,500 | AVAIL | 4000K |
| SWWOR2X4TRF3L50 | 2x4 | INTERNAL | AC 110 / 277V | 54W | 5,500 | AVAIL | 5000K |
| SWWOR2X4TRF4L30 | 2x4 | INTERNAL | AC 110 / 277V | 72W | 7,300 | AVAIL | 3000K |
| SWWOR2X4TRF4L40 | 2x4 | INTERNAL | AC 110 / 277V | 72W | 7,300 | AVAIL | 4000K |
| SWWOR2X4TRF4L50 | 2x4 | INTERNAL | AC 110 / 277V | 72W | 7,300 | AVAIL | 5000K |

