

Date: .	
Project:	:
Price:	
_	

Vapor Tight Jelly Jar

Description:

This rugged vapor-proof LED light is built to last. With industrial-grade rubber gaskets as sealants and automobile grade aluminum, this LED light is beacon against Mother Nature. With a COB Led inside, it provides performance lighting while utilizing very little power. With a die-cast guard on the outside of the glass, it protects docks, restaurants, and etc.

Features:

Input Power: AC 120V, 50/60 Hz

Wattage: 10W, 15W, 20W, or 30W

• CRI >90

CCT: 3000K, 3500K, 4000K, 5000K

 Available Mounting Options: Ceiling or Wall Mounted

Operating Temperature: -40 - 104F

L70 Lifetime: >50,000 hours.


• 0-10V dimming option available.


Lighting controls option available.

7 Year Warranty.

Dimensions

o 8.43 x 12.08IN

























Date:	
Project	:
Price:	
_	

Ordering Key:

ILDCVJJ				
SERIES NUMBER	WATTS/ SIZE/ LUMENS	ССТ	FINISH	ADDITONAL OPTIONS
ILDCVJJ	10 w - 8.4IN/ 900	3 - 3000K		DM - 0-10V DIMMING
	15 w - 8.4IN/ 1,100	35 - 3500K		
	20 w- 8.4IN/ 1,480	4 - 4000K		
	30 w- 8.4IN/ 2700	5 - 5000K		

SAMPLE ITEM NUMBER: ILDCVJJ 10 5 DM

Controls:

 This LED fixture is equipped with 0-10V dimming that works universally with any standard 0-10V control or dimmer.

Electrical Data:

• Input Power: Stays consistent over life.

• Input Voltage: 120-277 VAC

• **CRI:** >90

• L70 Lifetime: >50,000 hours.

Optical System:

- A unique combination of reflective & refractive optical components achieves a uniform, comfortable look while eliminating pixelation & color fringing.
- Parts work in unison to optimize light distribution, balancing the high delivery of high illuminance levels on horizontal surfaces with an ideal amount of light on walls and vertical surfaces, increasing perception of spaciousness.

















