

Date: .	
Project:	
Price:	
_	

LED STRIP/LED TANDEM STRIP FIXTURE



FEATURES:

- Available in lengths from 48 or 96 inches.
- Surface, stem, or chain mountable
- Snap on components for easy assembly and maintenance
- Steel channel (standard) with high-gloss, baked enamel finish
- Optional aluminum channel available
- Features corrosion-resistant fasteners for use in damp and harsh locations
- Combination end plates/channel connector furnished for either unit-mounted or continuos-row application
- White or specular reflectors available
- Channel cover retained by quarter-unit fastener
- Available sizes: 48"L x 12"W x 2.9"H
 96"L x 12"W x 2.9"H

CONSTRUCTION:

- Steel channel (standard) with high-gloss, baked polyester finish
- Combination end plates/channel connector furnished for either unit-mounted or continuos-row application
- Channel cover retained by quarter-turn fastener
- Optional aluminum channel available
- Features corrosion-resistant fasteners for use in damp and harsh locations

ILTFTSSL				
SERIES NUMBER	WATTS/ SIZE/ LUMENS	ССТ	FINISH	ADDITONAL OPTIONS
ILTFTSSL	15W - 4 FT / 2,100	3K - 3000K		DIM - 1-10V DIMMING
	16W - 4 FT / 2,240	4K - 4000K		EM - EMERGENCY BACKUP
	18W - 4 FT / 2,300	5K - 5000K		DIM - 0-10V DIMMING
	30W - 8 FT / 4,200			
	32W - 8 FT / 4,480			

SAMPLE ITEM NUMBER: ILTFTSSL 16W 4K EM

















