

# Melbourne LED Track Light

## Description:

Our Melbourne LED Track Light is well versed in color, wattage, and mounting options. This fixture can be used as a sconce, track light, or pendant with it's various mounting options.

## Features:

- 0-10V, Dali or Triac dimming, compatible with both ELV and MLV dimmer.
- Wattage: 8W, 10W, 15W, 22W, 38W, 42W
- Beam Spread: 15°/24°/38°/60°
- CRI >90
- Available Color Options: See below.
- Available Mounting Options: Ceiling mounted, suspended, track
- L70 Lifetime: >50,000 hours.
- Available Finish Options: Black, white or silver
- Lighting controls option available.
- 7 Year Warranty.
- Dimensions: 2.4" x 4.3" x 4.7"  
2.7" x 4.6" x 5.2"  
3.4" x 6.2" x 5.8"  
3.9" x 6.8" x 6.5"



**Style 1:**



The Only Style With A 42W Option

**Power Consumption: 8W, 10W, 15W, 22W or 42W**

**Finish: Black, White, Silver**

**Dimming: Triac dimmable track head, compatible with both ELV and MLV dimmer  
42W not dimmable**

**CCT: 2700K/3000K/3500K/4000K/5000K**

**Dimensions: 2.4" x 4.3" x 4.7" (8W), 2.7" x 4.6" x 5.2" (10W), 3.4" x 6.2" x 5.8" (22W), 3.9" x 6.8" x 6.5" (42W).**

**Style 2:**



**Power Consumption: 8W, 10W, 15W, or 22W**

**Finish: Black or White**

**Dimming: Triac and ELV dimming**

**CCT: 2700K/3000K/3500K/4000K/5000K**

**Compact diameter of 2 3/8" (8W), 2 3/4" (10W/15W), 3 3/16" (22W)**

**Style 3:**



**Power Consumption: 8W, 10W, 15W, or 22W**

**Finish: Black or White**

**Dimming: Triac and ELV dimming**

**CCT: 2700K/3000K/3500K/4000K/5000K**

**Compact diameter of 2 3/8" (8W), 2 3/4" (10W/15W), 3 3/16" (22W)**

**Style 4:**



**Power Consumption: 8W, 15W, or 22W**

**Finish: Black or White**

**Dimming: Triac and ELV dimming; Non-dim for 38W**

**CCT: 2700K/3000K/3500K/4000K/5000K**

**Compact diameter of 2 3/8" (8W), 2 3/4" (10W/15W), 3 3/16" (22W), 3 15/16" (38W)**

## Ordering Key:

SERIES NUMBER	STYLE	WATTS/ SIZE/ LUMENS	CCT	FINISH	ADDITIONAL OPTIONS
ILTLMBKL	S1 - STYLE 1	8W - 4 IN / 615	27K - 2700K	B - BLACK	DM - 0-10V DIMMING
	S2 - STYLE 2	10W - 4 IN / 860	3K - 3000K	W - WHITE	DD - DALI DIMMING
	S3 - STYLE 3	15W - 4 IN / 1,460	35K - 3500K	S - SILVER	DIM - TRIAC DIMMING
	S4 - STYLE 4	22W - 6 IN / 2,600	4K - 4000K		
		38W - 4IN / 4,800	5K - 5000K		
		42W* - 6 IN / 4,800			

\*Only Style 1 has a 42W option.

SAMPLE ITEM NUMBER: ILTLMBKL S2 15W 4K W DM

## Electrical Data:

- **Input Power:** Stays consistent over life.
- **Input Voltage:** 12V DC
- **CRI:** >90
- **L70** >50,000 hours.

## Controls:

- This LED fixture is equipped with 0-10V dimming that works universally with any standard 0-10V control or dimmer.

