



i-LUMINOSITY
LED LIGHTING FIXTURES

| | |
|----------|-------|
| Date: | _____ |
| Project: | _____ |
| Price: | _____ |

NOT YOUR EVERYDAY TRACK LIGHT

Description:

Our Not Your Everyday Track Light is well versed in color, wattage, and mounting options. This fixture can be used as a sconce, track light, or pendant with it's various mounting options.



Features:

- Triac dimmable, compatible with both ELV and MLV dimmer.
- Wattage: 8W, 10W, 15W, 22W, 38W, 42W
- Beam Spread: 15°/24°/38°/60°
- CRI >90
- Available Color Options: See below.
- Available Mounting Options: Ceiling mounted, suspended, track
- L70 Lifetime: >50,000 hours.
- Available Finish Options: Black, white or silver
- Lighting controls option available.
- 7 Year Warranty.
- Dimensions: 2.4" x 4.3" x 4.7"
2.7" x 4.6" x 5.2"
3.4" x 6.2" x 5.8"
3.9" x 6.8" x 6.5"





i-LUMINOSITY
LED LIGHTING FIXTURES

| | |
|----------|-------|
| Date: | _____ |
| Project: | _____ |
| Price: | _____ |

Style 1:



Power Consumption: 8W, 10W, 22W or 42W

Finish: Black, White, Silver

**Dimming: Triac dimmable track head, compatible with both ELV and MLV dimmer
42W not dimmable**

CCT: 2700K/3000K/3500K/4000K/5000K

Dimensions: 2.4" x 4.3" x 4.7" (8W), 2.7" x 4.6" x 5.2" (10W), 3.4" x 6.2" x 5.8" (22W), 3.9" x 6.8" x 6.5" (42W).

Style 2:



Power Consumption: 8W, 10W, 15W, or 22W

Finish: Black or White

Dimming: Triac and ELV dimming

CCT: 2700K/3000K/3500K/4000K/5000K

Compact diameter of 2 3/8" (8W), 2 3/4" (10W/15W), 3 3/16" (22W)

Style 3:



Power Consumption: 8W, 10W, 15W, or 22W

Finish: Black or White

Dimming: Triac and ELV dimming

CCT: 2700K/3000K/3500K/4000K/5000K

Compact diameter of 2 3/8" (8W), 2 3/4" (10W/15W), 3 3/16" (22W)

Style 4:



Power Consumption: 8W, 15W, or 22W

Finish: Black or White

Dimming: Triac and ELV dimming; Non-dim for 38W

CCT: 2700K/3000K/3500K/4000K/5000K

Compact diameter of 2 3/8" (8W), 2 3/4" (10W/15W), 3 3/16" (22W), 3 15/16" (38W)



i-LUMINOSITY
LED LIGHTING FIXTURES

| | |
|----------|-------|
| Date: | _____ |
| Project: | _____ |
| Price: | _____ |

Ordering Key:

ILTLMBKL

| SERIES NUMBER | STYLE | WATTS/ SIZE/ LUMENS | CCT | FINISH | ADDITIONAL OPTIONS |
|---------------|--------------|---------------------|-------------------|------------|-----------------------------|
| ILTLMBKL | S1 - STYLE 1 | 8W - 4 IN / 615 | 27K - 2700K | B - BLACK | DIM - Triac and ELV dimming |
| | S2 - STYLE 2 | 10W - 4 IN / 860 | 3K - 3000K | W - WHITE | |
| | S3 - STYLE 3 | 15W - 4 IN / 1,460 | 35K - 3500K | S - SILVER | |
| | S4 - STYLE 4 | 22W - 6 IN / 2,600 | 4K - 4000K | | |
| | | | 38W - 4IN / 4,800 | 5K - 5000K | |
| | | 42W* - 6 IN / 4,800 | | | |

*Only the track has a 42W option.

SAMPLE ITEM NUMBER: ILTLMBKL S2 15W 4K W DIM

Electrical Data:

- **Input Power:** Stays consistent over life.
- **Input Voltage:** 12V DC
- **CRI:** >90
- **L70** >50,000 hours.

Controls:

- This LED fixture is equipped with 0-10V dimming that works universally with any standard 0-10V control or dimmer.

Optical System:

- A unique combination of reflective & refractive optical components achieves a uniform, comfortable look while eliminating pixelation & color fringing.
- Parts work in unison to optimize light distribution, balancing the high delivery of high illuminance levels on horizontal surfaces with an ideal amount of light on walls and vertical surfaces, increasing perception of spaciousness.

