

Date:	_____
Project:	_____
Price:	_____

LED STRIP/LED TANDEM STRIP FIXTURE



FEATURES:

- Available in 4FT or 8FT
- Surface, stem, or chain mountable
- Snap on components for easy assembly and maintenance
- Steel channel (standard) with high-gloss, baked enamel finish
- Optional aluminum channel available
- Features corrosion-resistant fasteners for use in damp and harsh locations
- Combination end plates/channel connector furnished for either unit-mounted or continuous-row application
- White or specular reflectors available
- Channel cover retained by quarter-unit fastener
- Available sizes: 48"L x 12"W x 2.9"H
96"L x 12"W x 2.9"H

CONSTRUCTION:

- Steel channel (standard) with high-gloss, baked polyester finish
- Combination end plates/channel connector furnished for either unit-mounted or continuous-row application
- Channel cover retained by quarter-turn fastener
- Optional aluminum channel available
- Features corrosion-resistant fasteners for use in damp and harsh locations

ILFTSSSL

SERIES NUMBER	WATTS/ SIZE/ LUMENS	CCT	DRIVER	ADDITIONAL OPTIONS
ILFTSSSL	15W - 4 FT / 2,100	3K - 3000K	I - INTERNAL	DIM - 1-10V DIMMING
	16W - 4 FT / 2,240	4K - 4000K	E - EXTERNAL	EM - EMERGENCY BACKUP
	30W - 8 FT / 4,200	5K - 5000K		
	32W - 8 FT / 4,480			

SAMPLE ITEM NUMBER: ILFTSSSL 16W 4K E EM

E* - T24 compliant available for 16W or 32W



Date:	_____
Project:	_____
Price:	_____

Electrical Data:

- **Input power:** Stays consistent over life
- **Input Voltage:** 120-277VAC
- **Operating Temperature:** -40°F ~ 104°F
- **CRI:** >90
- **L₇₀ Lifetime:** >50,000 hours

Controls:

- This LED fixture is equipped with a 0-10V dimming driver that works universally with any standard 0-10V control or dimmer.
- This product can be equipped with a motion sensor option.

Optical System:

- A unique combination of reflective & refractive optical components achieves a uniform, comfortable look while eliminating pixelation & color fringing.
- Parts work in unison to optimize light distribution, balancing the high delivery of high illuminance levels on horizontal surfaces with an ideal amount of light on walls and vertical surfaces, increasing perception of spaciousness.

