

Date: .	
Project:	
Price:	
_	

LED INTEGRATED BOX FIXTURE

Description:

Our Integrated Box Fixture is a combination of your classic yet sleek fixture. With a high lumen output of 130 Lm/W and a CRI >90, this fixture achieves high levels of brightness and an even light spread, making it perfect for any application.



Features:

- Input Power: 120/277 VAC
- Power Consumption: 18W, 25W, 36W or 45W
- Lumen Output: 130Lm/W
- CRI >90
- Available Color Options: 3000K, 4000K, 5000K
- Housing Option: White Steel
- Available Mounting Options: Surface mount
- 1-10V dimmable option available.
- Allows for 3 -step down dimming from required light level to off.
- Emergency backup option available.
- Motion or Daylight sensor option available.
- Rated Life: >50,000 hours
- UL listed for damp location
- 7 Year Warranty
- Dimensions (L x H x W): 46.5" x 13.6" x 3.7"

Applications:

- **Stairways**
- **Storage Facilities**
- Hallways
- **Bathrooms**
- Basements Warehouses





















Date: _	
Project:	
Price:	
· · · · · _	

Ordering Key:

ILBXSBHL				
SERIES NUMBER	WATTS/ SIZE/ LUMENS	ССТ	FINISH	ADDITONAL OPTIONS
ILBXSBHL	18W - 2 FT. / 2,340	3K - 3000K	W - WHITE	DIM - 1-10V DIMMING
	25W - 4 FT. / 3,250	4K - 4000K		EM - EMERGENCY BACKUP
	36W - 4 FT. / 4,680	5K - 5000K		MS- MOTION SENSOR
	40W - 4 FT. / 5,200			
	45W - 4 FT. / 5,850			
	25W8FT. / 3,250			
	36W8FT . / 4,680			
	45W8FT. / 5,850			

SAMPLE ITEM NUMBER: ILBXSBHL 45W 5K EM MS

Electrical Data:

• Input Power: Stays consistent over life.

• Input Voltage: 120-277 VAC

• **CRI:** >90

• **L70 Lifetime:** >50,000 hours.

Controls:

- This LED fixture is equipped with 1-10V dimming that works universally with any standard 0-10V control or dimmer.
- This fixture has an emergency backup option available in event of a power outage.
- Motion sensor option is available for this product.

Optical System:

- A unique combination of reflective & refractive optical components achieves a uniform, comfortable look while eliminating pixelation & color fringing.
- Parts work in unison to optimize light distribution, balancing the high delivery of high illuminance levels on horizontal surfaces with an ideal amount of light on walls and vertical surfaces, increasing perception of spaciousness.



















Date:	
Project	:
Price:	
_	

Photometrics:





















