

Date:	
Project	:
Price:	

LED Mini Panel Light

Description:

Our LED Mini Panel Light ensures an even illumination across any surface. With a unique magnetic trim, our panels allow you to interchange the trim with a wide array of colors. Our Mini Panel can be surface mounted or recessed.

Features:

- Input Power: AC 120V, 50/60 Hz
- Housing Material: Thermal plastic cover & aluminum cooler inside with reflector cup
- Wattage: 6W/12W/18W/24W
- CRI >90
- CCT: 3000K, 4000K & 5000K options are built in to each fixture allowing you to change the CCT from 3000K to 5000K with the switch of a button.
- Available Mounting Options: Surface mounted or recessed.
- L70 Lifetime: >50,000 hours.
- Available Finish Options: Black, White, Rose Gold, Silver, or Bronze.
- 0-10V dimming option available.
- Lighting controls option available.
- 7 Year Warranty.
- Dimensions: 5.3 x .5

7.1 x .5

 $8.9 \times .5$

 $11.8 \times .5$





























Date:	
Project	:
Price:	
_	

Ordering Key:

ILMPLHO				
SERIES NUMBER	LUMENS/ WATTS/ SIZE/	CCT*	FINISH	ADDITONAL OPTIONS
ILMPLHO	360 - 6w / 5.3 IN	3 - 3000K	RG - RED GOLDEN	DM - 0-10V DIMMING
	840 - 12w / 7.1 IN	4 - 4000K	BB - BRUSHED BRONZE	
	1260 - 18w / 8.9 IN	5 - 5000K	BN - BRUSHED NICKEL	
	1920 - 24w / 11.8 IN		PB - POLISHED BLACK	
	400 - 6w / 5.3 IN		PC - POLISHED CHROME	
	1000 - 12w / 7.1 IN			
	1530 - 18w / 8.9 IN			
	1920 - 24w / 11.8 IN			

CCT*: 3000K, 4000K & 5000K options are built in to each fixture allowing you to change the CCT from 3000K to 5000K with the switch of a button.

SAMPLE ITEM NUMBER: ILMPLHO 840 4 BN DM

Electrical Data:

• Input Power: Stays consistent over life.

• Input Voltage: 120-277 VAC

• **CRI**: >90

• L70 Lifetime: >50,000 hours.

Controls:

• This LED fixture is equipped with 0-10V dimming that works universally with any standard 0-10V control or dimmer.

Optical System:

- A unique combination of reflective & refractive optical components achieves a uniform, comfortable look while eliminating pixelation & color fringing.
- Parts work in unison to optimize light distribution, balancing the high delivery of high illuminance levels on horizontal surfaces with an ideal amount of light on walls and vertical surfaces, increasing perception of spaciousness.

















