



i-LUMINOSITY
LED LIGHTING FIXTURES

Date:	_____
Project:	_____
Price:	_____

Prague Linkable Undercabinet Light

Description:

Our Linkable Undercabinet strip fixture ensures an even illumination across any surface, being that it's available in a variety of sizes & CCT options. This fixture is ideal for showcases, display cases and undercabinet.



Features:

- Input Power: 120/277V
- Power Consumption: 4W, 8W, 10W, 14W
- Beam Angle: 120°
- CRI >90
- Available Color Options: 3000K or 4000K
- Finish: White
- Available Length Options: 12", 22", 34", 46"
- Material: Plastic
- Operating Temperature: -4°F ~ 104°F
- L70 Lifetime: >50,000 hours
- Lighting controls option available.
- 7 Year Warranty

Dimensions:

(L) 12" / 22" / 34" / 46"
(H) 1.5"
(W) 1.0"



Date:	_____
Project:	_____
Price:	_____

Ordering Key:

SERIES NUMBER	SIZE/WATTS / LUMENS	CCT	FINISH
ILUCPLSL	124 - 12 Inches / 4W / 320LM	3 - 3000K	W - WHITE
	228 - 22 Inches / 8W / 640LM	4 - 4000K	
	3410 - 34 Inches / 10W / 800LM		
	4614 - 46 Inches / 14W / 1120LM		
	125 - 12 Inches / 5W / 500LM	CCT - 3000-4000K-5000K TUNABLE	
	229 - 22 Inches / 9W / 900LM		
	3412 - 34 Inches / 12W / 1200LM		
	4616 - 46 Inches / 16W / 1600LM		

SAMPLE ITEM NUMBER: ILUCPLSL 124 4 W

Electrical Data:

- **Input Power:** Stays consistent over life.
- **Input Voltage:** 120/277V
- **CRI:** >90
- **Operating Temperature:** -4°F ~ 104°F
- **L70 Lifetime:** >50,000 hours.

Controls:

- This LED fixture is equipped with 0-10V dimming that works universally with any standard 0-10V control or dimmer.

Optical System:

- A unique combination of reflective & refractive optical components achieves a uniform, comfortable look while eliminating pixelation & color fringing.
- Parts work in unison to optimize light distribution, balancing the high delivery of high illuminance levels on horizontal surfaces with an ideal amount of light on walls and vertical surfaces, increasing perception of spaciousness.

