



i-LUMINOSITY
LED LIGHTING FIXTURES

Date:	_____
Project:	_____
Price:	_____

LED Uptown Sconce

Description:

Our aluminum LED Uptown Sconce is up and down. It can be mounted outdoors with its IP65 rating. Encased in rounded cylindrical frame composed of high-quality aluminum, a corrosion-resistant material. Feel at ease with aluminum's high resilience, lasting quality, and inability to rust like steel. Power-coated hard surface provides phenomenal long-lasting color and exceptional corrosion/scratch resistance.



Features:

- Input Power: 120V
- Wattage: 12W *2 or 18W.
- IP65
- CRI >90
- Available Color Options: 3000K, 4000K, 6000K or RGB.
- Available Mounting Options: Wall mount
- Beam Angle: 15°/30°/60°/90°
- L70 Lifetime: >50,000 hours.
- Available Finish Options: Black or Grey
- 0-10V dimming option available.
- Lighting controls option available.
- 7 Year Warranty.
- Dimensions: 12W : 3.9 " x 11.8" or 18W: 6" x 12"



Date:	_____
Project:	_____
Price:	_____

Ordering Key:

SERIES NUMBER	WATTS/ SIZE/ LUMENS	CCT	FINISH	ADDITIONAL OPTIONS
ILPRGSSC	12w - 4IN / 1200	3 - 3000K	BL - BLACK	DM - 0-10V DIMMING
	18w - 6IN / 1800	4 - 4000K	G - GREY	
		6 - 6000K		
		RGB - RGB		

SAMPLE ITEM NUMBER: ILPRGSSC 12 3 BL DM

Electrical Data:

- **Input Power:** Stays consistent over life.
- **Input Voltage:** 120V
- **CRI:** >90
- **L70 Lifetime:** >50,000 hours.

Controls:

- This LED fixture is equipped with 0-10V dimming that works universally with any standard 0-10V control or dimmer.

Optical System:

- A unique combination of reflective & refractive optical components achieves a uniform, comfortable look while eliminating pixelation & color fringing.
- Parts work in unison to optimize light distribution, balancing the high delivery of high illuminance levels on horizontal surfaces with an ideal amount of light on walls and vertical surfaces, increasing perception of spaciousness.

