


### Features:

- Input Power: 120V
- Wattage: 12W, 18W, 12\*2 or 18W\*2.
- Waterproof: IP65 rating
- CRI >90
- Available Color Options: 3000K, 4000K, 6000K or RGB.
- Available Mounting Options: Wall mount
- Beam Angle: 15°/30°/60°/90°
- L70 Lifetime: >50,000 hours.
- Available Finish Options: Matte Black or Grey
- 0-10V dimming option available.
- Lighting controls option available.
- 7 Year Warranty.
- Dimensions: 12W: 3.9 " x 11.8" or 18W: 6" x 12"



(888)-998-LEDS (5337) | i-luminosity.com | info@i-luminosity.com












Uptown LED Sconce





#### **Ordering Key:**

ILSCUTPR			· <u> </u>		<u> </u>	
SERIES NUMBER	SIZE/LIGHT/WATTS/LUMENS	ССТ	BEAM ANGLE	POWER	FINISH	DIMMABLE
ILSCUTPR	4D12W - 4IN/DOWN/12W/600LM	<b>3K</b> - 3000K	<b>15</b> - 15°	<b>A</b> - AC 100-277V	B - BLACK	DM - 0-10V DIMMING
	6D18W - 6IN/DOWN/18W/900LM	<b>4K</b> - 4000K	<b>30</b> - 30°	<b>D</b> - DC 24V	<b>G</b> - GREY	
	4R24W - 4IN/UP-DOWN/12W/1200LM	<b>6K</b> - 6000K	<b>60</b> - 60°			
	6R36W-6IN/UP-DOWN/36W/1800LM	RGB - RGB	<b>90</b> - 90°			

SAMPLE ITEM NUMBER: ILSCUTPR 4D24W 3K 30 A B

### **Electrical Data:**

- Input Power: Stays consistent over life.
- Input Voltage: 120V
- **CRI:** >90
- L70 Lifetime: >50,000 hours.

## **Optical System:**

# **Controls:**

- This LED fixture is equipped with 0-10V dimming that works universally with any standard 0-10V control or dimmer.
- A unique combination of reflective & refractive optical components achieves a uniform, comfortable look while eliminating pixelation & color fringing.
- Parts work in unison to optimize light distribution, balancing the high delivery of high illuminance levels on horizontal surfaces with an ideal amount of light on walls and vertical surfaces, increasing perception of spaciousness.



(888)-998-LEDS (5337) | i-luminosity.com | info@i-luminosity.com