



Date:	_____
Project:	_____
Price:	_____

## Ordering Key:

SERIES NUMBER	SIZE/LIGHT/WATTS/LUMENS	CCT	BEAM ANGLE	O ER	FINISH	DIMMABLE
ILSC PR	2B 2GL BM L 4	3K - 3000K	15 - 15	A - AC 100-277V	B - BLACK	DM - 0-10V DIMMING
	4B 6 4GL B L 6 K	4 - 4000K	30 - 30	D - DC 24V	G - GREY	
	GL N B L K	6 - 6000K	60 - 60			
	4 4 4GL N B L 4 6 K	RGB - RGB	90 - 90			

SAMPL I M MB R ILSC PR 4D24W3 3 AB

## Electrical Data:

- **Input Power:** Stays consistent over life.
- **Input Voltage:** 120V
- **CRI:** >90
- **L70 Lifetime:** >50,000 hours.

## Controls:

- This LED fixture is equipped with 0-10V dimming that works universally with any standard 0-10V control or dimmer.

## Optical System:

- A unique combination of reflective & refractive optical components achieves a uniform, comfortable look while eliminating pixelation & color fringing.
- Parts work in unison to optimize light distribution, balancing the high delivery of high illuminance levels on horizontal surfaces with an ideal amount of light on walls and vertical surfaces, increasing perception of spaciousness.

