

Date: .	
Project:	:
Price:	
-	

Indirect Wave Linear

Description

Our Indirect Wave Linear is a perfect stand alone fixture. This fixture can be easily connected with additional options for emergency backup and dimming. This fixture is perfect for offices, retail spaces, conference rooms and many more applications.



• Power Consumption: 36W - 2 18W Tubes.

• Lumen Output: 4,000 Lm.

• L₇₀ Lifetime: >50,000 hours.

· Dimmable option available.

Beam Angle: 120.

· Housing Options Available: White.

Color Options Available: 4000K.

• Available Mounting Options: Suspended.

7 Year Warranty.

Applications:

Offices

Retail

Gyms

Malls

Schools

























Date: .	
Project:	:
Price:	
_	

Ordering Key:

ILLLIWSL				
SERIES NUMBER	SIZE/ WATTS/LUMENS	ССТ	FINISH	ADDITONAL OPTIONS
ILLLIWSL	36W - 4FT/ 4,000	4K - 4000K	W - WHITE	DIM - DIMMING
				EM -EMERGENCY BACKUP
				LK - LINKABLE

SAMPLE ITEM NUMBER: ILLLIWSL 36W 4K W DIM

Electrical Data:

Input Power: Stays consistent over life.

• Input Voltage: 100-277 VAC

• Operating Temperature: -4°F ~ 104°F

• CRI: >90

L70 Lifetime: >50,000 hours.

Controls:

 This LED fixture is equipped with 0-10V dimming that works universally with any standard 0-10V control or dimmer.

Optical System:

- A unique combination of reflective & refractive optical components achieves a uniform, comfortable look while eliminating pixelation & color fringing.
- Parts work in unison to optimize light distribution, balancing the high delivery of high illuminance levels on horizontal surfaces with an ideal amount of light on walls and vertical surfaces, increasing perception of spaciousness.

















