

Date:	_____
Project:	_____
Price:	_____

# LED Astoria Pendant

## Description:

Our LED Astoria Pendant is UL rated for damp locations. 12FT cord included. This fixture is ideal for industrial applications.

## Features:

- Input Power: AC 120-277V
- Power Consumption: 8W-25W
- Lumens Output: MAX 2,250
- Maximum 25 Watts.
- 12' Cord Included.
- Lighting control options available.
- L70 Lifetime: >50,000 hours
- CRI >90
- Available Color Options: 2700K, 3000K, 3500K, 4000K.
- Operating temperature: -40°F ~ 104°F
- Finish option: Black, White, Bronze, Green, Nickel, Red.
- 7 Year Warranty.
- Dimensions: (W) 10" or 12" (H) 11.5"



Date:	_____
Project:	_____
Price:	_____

## Ordering Key:

SERIES NUMBER	SIZE	CCT	FINISH	ADDITIONAL OPTIONS
ILPFAPBC	10IN - 10IN	27 - 2700K	BL - BLACK	
	12IN - 12IN	3 - 3000K	WH - WHITE	
		35 - 3500K	R - RED	
		4 - 4000K	BR - BRONZE	
			G - GREEN	

SAMPLE ITEM NUMBER: ILPFAPBC A19 3 BL

## Applications:

- Supermarkets
- Warehouse
- Indoor
- Office
- Industrial
- Retail

## Electrical Data:

- **Input power:** Stays consistent over life
- **Input Voltage:** 120-277VAC
- **Operating Temperature:** -40°F ~ 104°F
- **CRI:** >90
- **L70 Lifetime:** ~50,000 hours

## Controls:

- This LED fixture is equipped with a 0-10V dimming driver that works universally with any standard 0-10V control or dimmer.
- This product can be equipped with a motion sensor.
- Emergency backup option is available in event of a power outage.

## Optical System:

- A unique combination of reflective & refractive optical components achieves a uniform, comfortable look while eliminating pixelation & color fringing.
- Parts work in unison to optimize light distribution, balancing the high delivery of high illuminance levels on horizontal surfaces with an ideal amount of light on walls and vertical surfaces, increasing perception of spaciousness.

