



i-LUMINOSITY
LED LIGHTING FIXTURES

Date:	_____
Project:	_____
Price:	_____

Jackson Wrap Fixture

Description:

Our Jackson Wrap Fixture is available in both 2FT and 4FT options. This fixture can be used as a chain linked pendant or surface mounted. Easily linkable making it ideal for offices, retail, and residential applications.

Features:

- 120-277VAC or 120-347VAC
- Wattage: 20W, 35W, 48W, 64W, 100W
- 130LM/W
- Beam Spread: 120°
- CRI >90
- Available Color Options: 3000K, 4000K, 5000K.
- Available Mounting Options: Pendant Chained, Surface Mounted, and Linkable (Up to 8 PCS).
- L70 Lifetime: >50,000 hours.
- Finish: White.
- Additional Options: 0-10V Dimming, Triac Dimming, Microwave Sensor, Emergency Backup.
- Lighting controls option available.
- 7 Year Warranty.
- Dimensions:
24" X 5.51" X 2.77"
48" X 5.51" X 2.77"





i-LUMINOSITY
LED LIGHTING FIXTURES

Date:	_____
Project:	_____
Price:	_____

Ordering Key:

ILWRJWRD

SERIES NUMBER	VOLTAGE	WATTS/ SIZE/ LUMENS	CCT	FINISH	ADDITIONAL OPTIONS
ILWRJWRD	277 - 277VAC	20W - 24 IN / 2,600	3K - 3000K	W - WHITE	DIM - 0-10V dimming
	347 - 347VAC	35W - 24 IN / 4,550	4K - 4000K		TD - Triac dimming
		48W - 48 IN / 6,240	5K - 5000K		MS - Microwave Sensor
		64W - 48 IN / 8,320			EM - Emergency Backup
		100W - 48 IN / 13,000			LK - Linkable

SAMPLE ITEM NUMBER: ILWRJWRD 277 20W 3K W DIM

Electrical Data:

- **Input Power:** Stays consistent over life.
- **Input Voltage:** 120-277VAC or 120-347VAC
- **CRI:** >90
- **L70** >50,000 hours.

Controls:

- This LED fixture is equipped with 0-10V or Triac dimming that works universally with any standard Triac or 0-10V control or dimmer.

