

Warren Spotlight

Description:

Our Warren Spotlight is a sleek, high output fixture available in both square and round trims. This surface mounted luminaire has a variety of beam angle options and finishes to meet the criteria of most spaces. Ideal applications range from shopping malls, residential spaces, offices, corridors, and bathrooms, with it's IP44 rating.



Features:

- Input Voltage: 110-277V
- Wattage options: 25W or 30W
- Mounting options: Surface Mounted
- Dimensions:
 - Round: Diameter: 5.9" inches, Height 6.2" inches
 - Square: L: 5.9" inches, Width: 5.9" Inches, Height: 6.2" inches
- 0-10V Dimmable, Dali Dimmable, Triac Dimmable
- IP44 Rated
- CCT: 2700K, 3000K, 4000K
- Beam Angle: 50°, 60° or 80°
- CRI > 90
- Finish: White, Silver, Or Black
- 7 Year Warranty.



Ordering Key:

SERIES NUMBER	WATTS/ LUMENS /SHAPE	CCT	FINISH	ADDITIONAL OPTIONS
<div> <div>ILDLWRVZ</div> <div></div> </div>	25WR - 2,410 / ROUND	27K - 2700K	WH - WHITE	DIM - 0-10V DIMMING
	25WS - 2,410 / SQUARE	3K - 3000K	SL - SILVER	DAL - Dali Dimming
	30WR - 2,890 / ROUND	4K - 4000K	BL- BLACK	EM -EMERGENCY BACKUP
	30WS - 2,890 / SQUARE			5- 50° Angle
				6- 60° Angle
				8- 80° Angle

Sample Item Number: ILDLWRVZ 30WR 3K WH EM 6

Electrical Data:

- **Input power:** Stays consistent over life
- **Input Voltage:** 110-277VAC
- **CRI:** >90

Optical System:

- A unique combination of reflective & refractive optical components achieves a uniform, comfortable look while eliminating pixelation & color fringing.
- Parts work in unison to optimize light distribution, balancing the high delivery of high illuminance levels on horizontal surfaces with an ideal amount of light on walls and vertical surfaces, increasing perception of spaciousness.



Photometrics:

