

Warren Spotlight

Description:

Our Warren Spotlight is a sleek, high output fixture available in both square and round trims. This surface mounted luminaire has a variety of beam angle options and finishes to meet the criteria of most spaces. Ideal applications range from shopping malls, residential spaces, offices, corridors, and bathrooms, with it's IP44 rating.

Features:

- Input Voltage: 110-277V
- Wattage options: 6W, 10W, 15W, 20W, 25W or 30W
- Mounting options: Surface Mounted
- Dimensions:
 - Round:
 - (D) 3.1" inches, (H) 3.7" inches
 - (D) 4.9" inches, (H) 4.7" inches
 - (D) 5.9" inches, (H) 6.2" inches
 - Square:
 - (L): 3.1" inches, (W): 3.1" Inches, (H): 3.7" inches
 - (L): 4.7" inches, (W): 4.7" Inches, (H): 5.3" inches
 - (L): 5.9" inches, (W): 5.9" Inches, (H): 6.2" inches
- 0-10V Dimmable, Dali Dimmable, Triac Dimmable
- IP44 Rated
- CCT: 2700K, 3000K, 4000K
- Beam Angle: 45°, 50° or 60°
- CRI>90
- Finish: White, Silver, Or Black
- 7 Year Warranty.



Ordering Key:

SERIES NUMBER	SIZE	SHAPE	WATTAGE/ LUMENS	CCT	FINISH	BEAM ANGLE	ADDITIONAL OPTIONS
ILDLWRVZ	3 - 3 INCH	SQ - SQUARE	6W - 6W/630LM	27K - 2700K	WH - WHITE	45- 45°	DM - 0-10V DIMMING
	5 - 5 INCH	RD - ROUND	10W - 10W/1120LM	3K - 3000K	SL - SILVER	50- 50°	DD - DALI DIMMING
	6 - 6 INCH		15W - 15W/1600LM	4K - 4000K	BL - BLACK	60- 60°	TD - TRIAC DIMMING
			20W - 20W/2200LM				EM - EMERGENCY BACKUP
			25W - 25W/2326LM				
			30W - 30W/3177LM				

Sample Item Number: ILDLWRVZ 3 SQ 6W 27K WH 45 DM

Electrical Data:

- **Input power:** Stays consistent over life
- **Input Voltage:** 110-277VAC
- **CRI:** >90

Optical System:

- A unique combination of reflective & refractive optical components achieves a uniform, comfortable look while eliminating pixelation & color fringing.
- Parts work in unison to optimize light distribution, balancing the high delivery of high illuminance levels on horizontal surfaces with an ideal amount of light on walls and vertical surfaces, increasing perception of spaciousness.



Photometrics:

