

Date:	_____
Project:	_____
Price:	_____

Sirius LED Pendant

Description:

Our Sirius Pendants can be surface mounted or suspended. Offered with an array of reflectors and trim color options. These pendants are a smart energy saving solution for offices, lobbies, residential and retail locations.



Suspension

Surface Mount

Features:

- Input Power: AC 100-277V
- Light effect: 100LM/W
- Wattage Options:
Cylinder: 5W, 10W, 15W, 20W, 30W
Cuboid: 7W, 15W, 20W, 30W
- Color temperature: 2700K, 3000K, 3500K, and 4000K
- Dimming Options: On-off, Triac, 0-10V, Dali, and customized DMX
- Mounting Options: Surface or suspended.
- Beam Angle: 15°, 30°, 45°
- Housing Color: White, Black
- Reflector Color: Black, White, Silver, Golden.
- Operating temperature: -4° F - 149° F
- Waterproof Options: IP20, IP44, and IP65
- L70 Lifetime: >50,000 hours.
- 7 Year Warranty.



Applications:

- Shops
- Schools
- Offices
- Museums
- Conference Rooms
- Hospitals
- Corridors
- Hotel

Dimensions:

Cylinder



Cylinder	D(Inch)	H(Inch)
5W	2.13	3.88
10W	3.00	5.13
15W	3.00	5.75
20W	4.50	6.25
30W	5.63	6.38

Cuboid



Cuboid	L(Inch)	W(Inch)	H(Inch)
7W	2.13	2.13	4.75
15W	3	3	5.5
20W	3.75	3.75	6.25
30W	4.5	4.5	6.25



Date:	_____
Project:	_____
Price:	_____

Ordering Key:

SERIES NUMBER	SIZE/SHAPE	CCT	HOUSE FINISH	REFLECTOR FINISH	BEAM ANGLE	DIMMABLE	ADDITIONAL OPTION
ILPFSRDT	2R5W - 2.13" Cylinder / 5W	27K - 2700K	B - BLACK	B - BLACK	18 - 18°	DM - 1-10V	P - Pendant
	3R10W - 3" Cylinder / 10W	3K - 3000K	W - WHITE	G - GOLD	30 - 30°	DD - DALI	S - Surface mount
	3R15W - 3" Cylinder / 15W	35K - 3500K		S - SILVER	45 - 45°	TD - TRIAC	IP20 - IP20
	5R20W - 4.5" Cylinder / 20W	4K - 4000K		W - WHITE			IP44 - IP44
	6R30W - 5.63" Cylinder / 30W						IP65 - IP65
	2Q7W - 2.13" Cuboid / 7W						EM - Emergency Backup
	3Q15W - 3" Cuboid / 15W						
	4Q20W - 3.75" Cuboid / 20W						
	5Q30W - 4.5" Cuboid / 30W						

SAMPLE ITEM NUMBER: ILPFSRDT 3R15W 3K B B 35 DM P IP44

Electrical Data:

- **Input Power:** Stays consistent over life.
- **Input Voltage:** AC 100-277V
- **CRI:** >90
- **L70 Lifetime:** >50,000 hours.

Optical System:

- A unique combination of reflective & refractive optical components achieves a uniform, comfortable look while eliminating pixelation & color fringing.
- Parts work in unison to optimize light distribution, balancing the high delivery of high illuminance levels on horizontal surfaces with an ideal amount of light on walls and vertical surfaces, increasing perception of spaciousness.

Construction:

- **Construction:** Heatsink aluminum housing.
- **Glare:** Unified glare rating (UGR) <19 making it easy on the eyes in offices or work settings.
- **Suspension Cable length:** 2FT

